

# PC2 Roller Chain

Capacities: 3/4 to 15 Ton



Single or double locking pawl design

Roller chain is easily spliced to change lift or replace worn links

Hardened alloy steel roller chain designed for hoist duty

## PC2 Roller Chain Model

Malleable iron roller chain ratchet lever hoists are efficient and durable. Roller chain can be spliced to create longer lifts and can handle higher capacities than coil chain. PC2 hoists are ideal for utility transmission and distribution work.

- **Capacities & Lift-** Rated loads from 3/4 to 15 Tons. For standard lift, see chart. Other lifts available.
- **Rugged-** Unit and handle made from malleable iron. Riveted construction makes the unit tamper-resistant.
- **Free Chaining-** Free chaining mechanism allows quick and easy take-up and positioning of slack chain. Hoist will not free chain when under load.
- **Handle Stops-** Prevent handle from spinning if it is accidentally released by the operator.
- **Single or Double Locking Pawl Design**
- **Multiple Rigging Options-** Hoist can lift, pull, or bind. Can be operated from either side and will work in any position with equal efficiency.
- **Snap Hook and Link-** Allows operator to convert unit to next smaller capacity to give longer lift and faster operation. Snap hook acts as an end stop and will not pass through chain sprocket.
- **Options-** Bullard hooks, bronze hooks, and zinc-plated hooks—consult factory.
- **Lifetime Warranty**

## PD2 & PC2 Specifications

	Product Code Number†	Rated Capacity in Tons	Standard Lift (in.)	Strands of Load Chain	Minimum Distance Between Hooks (in.)	Handle Length Inches (in.)	Average Handle Effort (lbs.)	Net Weight (lbs.)
PD2 Models	931-04107	3/4	60	1	12 1/2	17 1/2	87	18
	931-06107	1 1/2	60	1	15	17 1/2	71	29
	931-09107	3	60	1	15 1/2	22 1/2	91	41
PC2 Models	Y05101	3/4	56 1/2	1	13	18 3/4	56	18
	Y05103	3/4	56 1/2	1	13	18 3/4	56	18
	Y05105	1 1/2	57	2	15	18 3/4	60	22
	Y05107	1 1/2	57	2	15	18 3/4	116	23
	Y05109	1 1/2	56 1/2	1	16	27 5/8	116	29
	Y05111	1 1/2	56 1/2	1	16	27 5/8	120	35
	Y05113	3	57	2	17 5/8	27 5/8	120	39
	Y05115	3	57	2	17 5/8	27 5/8	124	45
	Y05117	4 1/2	53	3	25	33 5/8	124	56
	Y05119	6	53	4	25	33 5/8	124	68
	Y05127	15	60	8	30	33 5/8	124	152

†First designation is single pawl model and second "I" designation is double pawl model.