

# RS2 Link Chain

Capacities: 3/4 to 3 Ton



## Thousands of uses throughout all types of industries

— maintenance, ship building, construction, steel fabrication, utility work, mining, petrochemical, etc.

Ideal for moving or spotting heavy machinery, pulling utility lines taut, stretching cables or fencing. Holds steel structural members in place for welding. Simplifies setting pipes, meters, etc. in manholes and trenches.

- Easy one-hand operation.
- Lever pull range is 45 to 62 pounds to lift full load.
- Handle that rotates 360°, making it easy to operate in any position and in small spaces.
- Tough yet lightweight aluminum construction and powder coat finish.
- Hoist alloy hardened steel load chain for strength, long wear life and flexibility.
- Free chaining for fast, easy attachment to load.
- Forged upper and lower hooks with latches.
- Double pawl for precise load spotting
- Simple construction with fewer parts for ease of maintenance.
- Optional Load Limiter device protects against overload.
- Lifetime warranty.
- Made in U.S.A.

## PE2 & RS2 Specifications

	Rated Capacity* (Tons)	Product Code No.	Standard Lift† (ft.)	Pull to Lift Full Load (lbs.)	Minimum Distance Between Hooks (in.)	Lever Length (in.)	Strands of Load Chain	Hook Throat Openings (in.)	Approx. Shipping Weight (lbs.)
PE2 Models	3/4	931-04108	5	58	10 3/4	21 1/4	1	1 1/32	16
	1 1/2	931-06108	5	89	14 1/4	21 1/4	1	1 1/8	26
	3	931-09108	5	95	16 15/16	21 1/4	2	1 7/32	38
	6	931-14108	5	96	21 3/8	21 1/4	4	1 3/4	73
RS2 Models	3/4	935-04101	5	45	12 1/4	12	1	1 1/32	16
	1 1/2	935-06101	5	55	14 3/4	16 3/4	1	1 1/8	27
	3	935-08101	5	62	17 5/8	16 3/4	2	1 3/16	40

†Can be supplied with lifts longer than 5 feet